



# HOT TAR & ASPHALT HOSE

PRODUCT DESIGN & ENG. DIVISION

2016. 9. 19

## Product Specifications

- Application : This hose is designed for the suction & discharge of hot tar and asphalt.
- Tube : Black NBR synthetic rubber
- Reinforcement : Spiral-plied synthetic fabric with helix wire
- Cover : Black NBR synthetic rubber

Temperature	-40°F to 350°F (-40°C to 175°C)		
Safety Factor	4:1	Max. Lengths	200ft / 60m
Vacuum	737mmHg / 29inHg		
Branding	HOT TAR & ASPHALT HOSE 150 PSI MAWP		

Part No.	I.D		O.D		MAX. W.P		Bend Radius		Approx. Weight	
	Inch	mm	Inch	mm	Psi	Bar	in	mm	lbs/ft	kg/m
* Smooth Cover										
-	1-1/2"	38.1	2.15	54.5	150	10	10	250	1.26	1.87
-	2"	50.8	2.65	67.2	150	10	12	300	1.61	2.39
-	2-1/2"	63.5	3.17	80.4	150	10	16	400	1.98	2.94
-	3"	76.2	3.68	93.5	150	10	20	500	2.39	3.56
-	4"	101.6	4.75	120.6	150	10	28	700	3.34	4.97